



Analog Input Modules

8-channel analog input modules, 12-bit resolution



M-3802: 8 analog inputs, 4 to 20 mA, 12 bits

Analog Inputs: 8 channels
Resolution in Ranges: 12 bits, 3.91 μ A/bit
Input Current Range: 4 to 20 mA (single-ended)
Data Format: 16-bit integer (2's complement)
Accuracy:
 • $\pm 0.1\%$, FSR @ 25°C
 • $\pm 0.3\%$, FSR @ 0°C, 60°C
Input Impedance: 120 ohms
Conversion Time: 4 ms for all channels
Power Consumption: 80 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 7,375,920 hrs (Database: Telcordia/Bellcore)



M-3810: 8 analog inputs, 0 to 10 V, 12 bits

Analog Inputs: 8 channels
Resolution in Ranges: 12 bits, 2.44 mV/bit
Input Current Range: 0 to 10 VDC (single-ended)
Data Format: 16-bit integer (2's complement)
Accuracy:
 • $\pm 0.1\%$, FSR @ 25°C
 • $\pm 0.3\%$, FSR @ 0°C, 60°C
Input Impedance: 500K ohms
Conversion Time: 4 ms for all channels
Power Consumption: 60 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 7,288,320 hrs (Database: Telcordia/Bellcore)



Ordering Information

Available Models

M-3802: Modular remote I/O module with 8 AIs, 4-20 mA, RTB, -10 to 60°C operating temperature

M-3810: Modular remote I/O module with 8 AIs, 0-10 VDC, RTB, -10 to 60°C operating temperature